ASTROFLAME
PASSIVE FIRE STOP SYSTEMS

Product Data Sheet

Astro FR Door Viewer

Revision 6 - 21st February 2022



Astroflame (Fireseals) LTD : Unit 8 , I.O Centre : Stephenson Road : Segensworth : Fareham : PO15 5RU
T - **01329 844500** : **W** - **www.astroflame.com** : **E** - **sales@astroflame.com**

Astro FR Door Viewer

Fire Rated Door Viewer



- Solid Brass body.
- Up to 60 minutes Fire Rated for Timber Fire Doors.
- Up to 30 minutes Fire Rated for Composite Doors.
- Comprises of 3 pyrex glass lenses.
- Privacy cover included.
- Suits 35mm - 55mm thickness doors.
- 120 degree viewing angle.
- **Brand New** Black finish.
- Brass or Chrome finish.



Product Description

The Astroflame Fire Rated Door Viewer is suitable for standard size thicknesses of 35mm - 55mm and is fire rated up to 60 minutes on timber fire doors and up to 30 minutes fire rated for composite doors.

Offering 120 degree view and made from solid brass with 3 Pyrex glass lenses with a 14mm barrel.

Conforms to DHF TS002 : 2009 Specification.

Product Availability

Product Code	Product Description	Colour
AFDV14BLK	Astro FR Door Viewer	Black
AFDV14B	Astro FR Door Viewer	Brass
AFDV14C	Astro FR Door Viewer	Chrome

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Colour
Typical example:- 6 / AFDV14B / Astro FR Door Viewer / Brass

>> Tel: 01329 844 500 or >> Email: sales@astroflame.com

Installation

We have technical representatives who provide assistance in the selection and specification of the products on this site and should be consulted for exact installation and product suitability. Ensure an early engagement with ourselves, designers, main contractor and specialist installers before any installation. Other trades and/or manufacturers may need to be consulted. For in-depth information, specification and technical advice please call our Head Office on tel 01329 844 500 or email sales@astroflame.com

Maintenance

All interested parties, designer, specifier, main contractor and specialist installers should provide access to allow the fire stopping seals to be regularly inspected and maintained, as well as records kept of such maintenance at minimum periods of 12 months, as required by the Regulatory Reform Order, and repaired if necessary. Reference should be made to ASFP TGD 17 – Code of Practice for the Installation and Inspection of Fire Stopping.

Competency

It is vital that those entrusted to design or install a fire stopping product have the necessary levels of competence to undertake the task professionally and thoroughly. The level of competency required will be commensurate with the expected complexity of the building. All designers must eliminate, reduce or control foreseeable risks that may arise during installation, construction or maintenance when preparing or modifying designs. Clients should ensure that the principal designer and principal contractor carry out their duties under CDM regulations. The ASFP foundation course in passive fire protection provides essential knowledge as part of demonstrating competency and understanding in this key fire protection specialism.

Additional Notes

Each fire door and hardware component will have its own test evidence. It is the responsibility of the purchaser to ensure that the product is fully compliant with the relevant test evidence, if in doubt please contact the technical team on: tel 01329 844 500 or email sales@astroflame.com

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: 01329 844 500 or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME (FIRE SEALS) LTD has no control over the specific application or installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product based on the products limitation of applications and that the product is fit for purpose for their intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROFLAME (FIRE SEALS) LTD, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice. If you are in any doubt as to the suitability of this product for your intended application please contact our technical team on 01329 844500 or email sales@astroflame.com and we will contact you.